



Duct Tape 1900

Product Data Sheet

December 2008

Supersedes: Draft August 2008

Product Description

3M Duct Tape 1900 is a conformable cloth duct tape, made with a polyethylene coated cloth scrim and synthetic rubber adhesive. Duct Tape 1900 is a good choice for non-critical applications.

Key Features

Duct tape 1900 can be used for many purposes: masking, marking, light duty sealing and holding, bundling.

Advantages

Easy tear, low profile, Polyethylene backing provides moisture resistance to tape applications, synthetic rubber adhesive sticks well to many surfaces.

Benefits

Good curve masking and wrapping irregular surfaces, easy handling, can be used in combination with humidity, conformable, individually wrapped roll for easy identification and to keep the roll clean until ready for use.

Typical Physical Properties

Adhesive	Synthetic rubber/resin
Backing	Polyethylene coated cloth scrim
Colour	Silver and black
Thickness (AFERA 5006)	0,17 mm

Performance Characteristics

Note: the following technical information and data should be considered representative or typical only and should not be used for specification purposes

Adhesion to stainl. steel (AFERA 5001)	15 N/25 mm
Tensile strength (AFERA 5004)	70 N/25 mm
Elongation (AFERA 5004)	20 %
Temperature resistance	60°C max.

Storage

Store in clean dry place. Temperature of 21 °C and 50 percent relative humidity are recommended.

Shelf Life

3M 1900 has a shelf life of 6 months from date of despatch by 3M when stored in the original carton at 21°C (70°F) & 50 % relative humidity.

For Additional Information

To request additional product information see address below.

Important Notice

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law

Note

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M is a trademark of the 3M Company.

3M United Kingdom PLC 3M House, 28 Great Jackson Street, Manchester, M15 4PA	Product Information : Tel 0870 60 800 50 Fax 0870 60 700 99	3M Ireland Limited The Iveagh Building The Park, Carrickmines Dublin 18, Ireland	Customer Service : Tel (01) 280 3555 Fax (01) 280 3509
--	---	--	--