



Scotch™ Tape 3030

Premium Auto Refinish Masking Tape

Product Data Sheet

Date: December 2010
Supersedes: New

Product Description Scotch™ Tape 3030 is a green coloured smooth creped paper masking tape designed for a wide variety of applications in the auto refinishing market for applications up to 100°C where superior water resistance is expected

Key Features Latex saturated medium weight smooth crepe paper backing
Light green colour
Controlled crosslink rubber resin adhesive

Advantages Excellent solvent and superior water resistance
Good conformability with easy hand tear and controlled unwind
Surface smoothness promotes good clean paint line and prevents paint bleed through
Improved paint flaking and wetting performance
Good instant adhesion and superior holding power
Excellent adhesive transfer and removability performance

Benefits Performs well with water based paint systems
No need to re-mask after wet sanding
Sticks easily and resists lifting
Clean removal and resists slivering

Physical Properties

Adhesive	Rubber / Resin
Backing	Paper
Colour	Green
Thickness (AFERA 5006)	0,130mm

Performance Characteristics

* Note: the following technical information and data should be considered representative or typical only and should not be used for specification purposes

Adhesion to steel (AFERA 5004)	8.5 N/25mm
Tensile strength (AFERA 5004)	80 N/25mm
Elongation (AFERA 5004)	10%
Temperature performance	100°C max.

Application details

The temperature performance of the Scotch™ Tape 3030 allows air drying and oven curing of paint up to 100°C for one hour single pass, or at lower temperatures for lower bake cycles

Available Sizes	Width (mm) : 15, 19, 25, 30, 38, 50, 75, 100 Length (m) : 50
Storage	Store in a clean dry place. Temperature of 21°C and 50 percent relative humidity are recommended
For additional information	To request additional information see address below
Important notice	All statements, technical information and recommendations contained in this document are based upon test or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of sale subject, where applicable, to the prevailing law
Note	Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable, but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M is a trademark of the 3M company
Scotch is a trademark of the 3M company

3M UK PLC
5-7 Balloo Drive
Balloo Industrial Estate
Bangor
County Down
Northern Ireland
BT19 7PB
Tel: +44 2891 278200
Fax: +44 2891 451072
Internet: www.3M.com