



TECHNICAL DATA

Scapa 3130

Matt Waterproof Cloth Tape

DESCRIPTION

Scapa 3130 is a high quality 80 mesh, polyethylene coated waterproof cloth tape, coated with a pressure sensitive adhesive and a superior matt finish.

Scapa 3130 is available in a range of standard colours including black, white, blue, red, green and yellow, plus the specific shades Chromakey blue and green for the entertainment industry.

APPLICATIONS

- Temporary fixing and holding of wires and cables to floors and walls
- Masking of stage equipment
- Colour coding and identification
- Floor marking
- Joining and splicing applications
- Book and spine binding
- Masking applications such as unwanted film set items
- Ideal for general purpose applications where added strength, performance and low light reflectance is required

PRODUCT BENEFITS

- Excellent Matt finish prevents the reflection of light
- Excellent waterproof properties
- Good strength
- Can be removed cleanly from surfaces after being in situ temporarily*
- Highly flexible and conformable to support use in difficult and uneven surfaces
- Good initial tack and ultimate adhesion
- Easy unwind for ease of use
- Very easy tear by hand
- Peels off cleanly after use, even after 6 weeks*
- Can be written on
- Good all round performance

*as tested under specific laboratory conditions

Issue : 5

Date : 01.02.12

Page 1 of 2

3130.doc

www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer.

TECHNICAL PROPERTIES

| | Unit | Nominal Value | Test Method |
|---------------------|------|---------------|-------------|
| Thickness | mm | 0.29 | Internal* |
| Tensile Strength | N/cm | 55 | IEC 454-2 |
| Adhesion to Steel | N/cm | 3 | IEC 454-2 |
| Adhesion to Backing | N/cm | 1.5 | IEC 454-2 |
| Service Temperature | °C | 0-60°C | |

*Scapa Internal Test Method

STANDARD PRESENTATION

- Roll Length: 50m
- Roll Width: 25mm, 38mm, 50mm, 75mm, 100mm
- Core: 76mm Cardboard
- Packaging: Bulk packed using interleaving sheets between layers

Note: Information on stock items, non standard sizes and lead times is available on request

RECOMMENDATIONS

*The rolls should be stored flat on their cut edges in the original packaging, until required for use.
The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes.*

The shelf life will vary depending on conditions of storage but should not be less than two years from the date of manufacture, if stored in a moderate climate and good conditions.