



# Scapa 3160PA

## 3160PA Waterproof Cloth Tape - Glazing

## **DESCRIPTION**

Scapa 3160PA is a standard grade waterproof cloth tape, coated with a pressure sensitive natural rubber resin adhesive. The product has been designed for use in the glazing market and is suitable for a range of general purpose applications.

#### **APPLICATIONS**

- Designed for use in double glazed unit sealing
- Used for general purpose sealing, bundling, short term masking and protection

## **PRODUCT BENEFITS**

- Easy unwind by hand
- Good water resistance
- · Good adhesion and ultimate bond strength
- Easy tear by hand
- Flexible and conformable

## **TECHNICAL PROPERTIES**

Technical Property	Nominal Value	Unit	Test Method
Thickness	0.15	mm	AFERA 5006
Adhesion to Steel	4.5	N/cm	IEC 454-2
Adhesion to Backing	2.5	N/cm	IEC 454-2
Tensile Strength	35	N/cm	IEC 454-2
Service Temperature Range	0-70	°C to °C	-

Version: 2 Generated Date: 12 June 2018 Page: 1 of 2

www.scapa.com Product Code: 3160PA

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

#### STANDARD PRESENTATIONS

• Branding: Available on plain or Scapa core

• Roll Length: 50m

• Roll Width: 44 and 50mm. Others sizes on request subject to volume and availability

#### **RECOMMENDATIONS**

The rolls should be stored flat on their cut edges in their original packaging, until required for use. It is necessary to protect the product from dust, heat, moisture, direct sunshine and solvent fumes and stored in a moderate climatic conditions. Shelf life will vary with conditions of use but should be not less than two years from date of manufacture.

Version: 2 Generated Date: 12 June 2018 Page: 2 of 2

www.scapa.com Product Code: 3160PA