

tesa 4156 PV 1

Specialty tape for film masking

Product Description/ Application:

tesa 4156 PV 1 is a specially tape designed for film and negative masking. The tape is available as litho-red (colour 57).

- tesa 4156 PV 1 is light and age resistant and is easily removed without splitting or tearing. It also does not leave adhesive residues.
- tesa 4156 PV 1 is easily applied as the tape lies flat during positioning and is not prone to edge curling.
- tesa 4156 PV 1 ensures secure masking with perfect edge definition.

- tesa 4156 PV 1 is highly transparent to the human eye even without the use of a light table. Parts already masked therefore remain visible thus enabling accurate positioning of the tape.
- Due to its special properties tesa 4156 PV 1 is also suitable for splicing of film
- tesa 4156 PV 1 is recommended for use with tesa litho dispensers 6082 and 6090. Specially designed for litho work the straight-edge blade does not leave a serrated edge.

Dimensions:

Stock items	
Length:	66 m
Widths:	12, 25, 50 mm

Other dimensions on enquiry.

Technical Data: (mean values)

Backing	Colour	Thickness ¹⁾	Adhesion/ steel ¹⁾	Elongation at break ¹⁾	Tensile strength ¹⁾
cellophane	litho-red (57)	0,06 mm	8,75 N/25 mm	25 %	127 N/25 mm

¹⁾ Parameters of the specification

3510 - 04/01

BDF●●●●●

Beiersdorf AG

Unnastraße 48

D-20245 Hamburg

Telephone +49-40-49 09 3360

Telefax +49-40-49 09 4506

tesa self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The Advisory Section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.



Quality
management

Internal page - Product information

Product name and -number: 4156 PV1

Date of last Version:	Date of Alteration	Subject of Alteration	Kst / PM	Kst. / F & E
07/97	04/01	Change of measures from N/cm to N/25 mm		3236 / Pletz

BDF●●●●

Beiersdorf AG

Unnastraße 48

D-20245 Hamburg

Telephone +49-40-49 09 3360

Telefax +49-40-49 09 4506

tesa self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The Advisory Section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.