PRODUCT INFORMATION

tesa 4323 General Purpose Paper Masking Tape

Product Description/	tesa 4323 is a finely crêped	•
Application:	paper masking tape with a natural rubber adhesive.	masking, holding, sealing, fix- ing, light duty packaging e.t.c.

		-	
1 110	nnn	CIA	nci
DII	nen	310	113.

Standard length:	50 m
Widths:	15, 19, 25, 30, 38, 50,75mm

Other dimensions on enquiry.

Technical Data: (mean values)

Backing:	sligthly creped paper	Tensile strength: ¹⁾	90 N/25 mm
Total Thickness: ¹⁾	130 µm	Elongation at break: ¹⁾	10 %
Adhesive strength: ¹⁾	7,5 N/25 mm	Temperature resistance: ²⁾	up to 50 °C short term

¹⁾ Parameters of the specification

²⁾ Application property

3520 - 06/97

BDF入入入入 Beiersdorf AG Unnastraße 48 D-20245 Hamburg Telephone +49-40 49 09 2618 Telefax +49-40-49 09 6113 tesa self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The Advisory Section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.

BDF λλλλ Tesa °	Marketing	Interne Seite der Produktinformation	ldent-Nr.: Version: Gültig ab:	001	
Produktbezeichnung incl. Produktnummer: tesa 4323		Seite	1 von	1	

Date of last Version:	Date of Alteration	Subject of Alteration	Kst / PM	Kst. / F & E

tesa self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The Advisory Section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.