

## tesa® 4334 Precision Mask®

High grade paper masking tape for precise and flat paint edges

tesa® 4334 Precision Mask consists of an extra-thin and strong paper backing coated with an acrylic adhesive.

The combination of the highly equipped backing material and the outstanding special adhesive formulation allows easy removability up to 6 months Indoors and 8 weeks Outdoors after application. This enables multiple working processes in only one covering process.

### Main Application

This tape is suited for almost all indoor and outdoor painting applications.

tesa® 4334 Precision Mask is suitable for use with water-based paints and lacquers and even for spatula application techniques.

It is suitable for a variety of common surfaces such as glass, aluminium, hard-PVC and wood.

It is especially suited for applications when a precise razor-sharp paint edge is needed.

- Indoor masking (up to 6 months)
- Outdoor masking (up to 8 weeks)
- For use on smooth and slightly textured surfaces
- For high-quality painting and lacquering work
- For spray painting with afterwards oven drying up to 120°C/30 min

### Technical Data

▪ Backing material	flat paper	▪ Elongation at break	4 %
▪ Total thickness	90 µm	▪ Tensile strength	30 N/cm
▪ Type of adhesive	acrylic	▪ UV-resistance	8 weeks
▪ Adhesion to steel	1.85 N/cm		

### Properties

▪ Hand tearability	●●●●	▪ Paint anchorage	●●●●
▪ Suitable for sensitive surfaces	●●●	▪ Sharp colour edge	●●●●
▪ Suitable for rough surfaces	●●●	▪ Conformability	●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04334>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.