

tesa® Professional 4440 Precision Mask® Outdoor

Painter's tape for professional paint jobs outdoors

tesa® 4440 Precision Mask® Outdoor consists of an extra-thin and strong washi paper backing coated with an acrylic adhesive.

The combination of the highly equipped backing material and the outstanding special adhesive formulation allows easy removability up to 26 weeks after application outdoors. This enables multiple working processes in only one covering process.

Main Application

- Professional paint jobs outdoors (up to 26 weeks)
- Light plasterwork tasks
- Ideal for sharp paint edges
- Also suitable for rough surfaces

Technical Data

▪ Backing material	flat paper	▪ Elongation at break	5 %
▪ Total thickness	110 µm	▪ Tensile strength	35 N/cm
▪ Type of adhesive	acrylic	▪ UV-resistance	26 weeks
▪ Adhesion to steel	1.8 N/cm		

Properties

▪ Hand tearability	● ● ● ●	▪ Sharp colour edge	● ● ● ●
▪ Suitable for sensitive surfaces	● ●	▪ Smooth colour edge	● ● ● ●
▪ Suitable for rough surfaces	● ● ●	▪ Conformability	● ● ● ●
▪ Paint anchorage	● ● ● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

Additional Information

The application of an adhesive tape on weathered surfaces may lead to residues during the de-masking. Thus before using an adhesive tape on a weathered surface we recommend to make a trial application for up to 24 hours

For latest information on this product please visit <http://l.tesa.com/?ip=04440>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.