# productinformation

## tesa® 4668

#### Professional transparent duct tape

tesa® 4668 is a polyethylene tape based on a transparent PE film and an acrylic adhesive. tesa® 4668 is a very strong tape for a wide range of applications, often used for splicing of LDPE films in constructions and house buildings. Features:

- excellent UV resistance
- strong, ageing-resistant adhesive
- weather- and waterproof
- good abrasion resistance
- very good resistance to solvents
- approved by the Swedish Institute for Technical Approval in Contruction (SITAC) for splicing of polyethylene film in constructions

### Main Application

- Indoor and outdoor applications
- Repairing of plastic materials
- Affixing LDPE films in construction applications
- Sealing of plastic bags
- Transparent film for nearly invisible repairs

#### Technical Data

•	Backing material	PE film	•	Elongation at break	500 %
•	Total thickness	140 μm	•	Tensile strength	20 N/cm
•	Type of adhesive	acrylic	•	Temperature resistance (30 min)	95 °C
•	Adhesion to steel	3.4 N/cm	•	UV-resistance	24 weeks

#### **Properties**

•	Hand tearability	• •	•	Abrasion resistance	• • •
•	Certified according to	SITAC	٠	Water resistance	••••

Evaluation across relevant tesa® assortment: •••• very good •• good •• medium • low

Page 1 of 1 - As of 10/01/3

tesa\*