

# tesa 51006 PET cloth tape for manual bundling of wire harnesses in the engine compartment

# **Product Description:**

### Features:

- rot proof
- chemical resistant
- abrasion resistant
- flexible and smooth
- tear resistant
- stable unwind strength
- resistant to ageing
- strong adhesion

#### Benefits:

- tesa 51006 meets the high temperature requirements of applications in the engine compartment.
- Its stable unwind strength allows easy wrapping.

## **Dimensions:**

Length	Widths	Inner core diameter
25 m	9, 19 mm	38 mm

Other dimensions on enquiry

### Technical Data:

Backing:	PET cloth	Tensile strength: <sup>1)</sup>	≥ 150 N/cm
Adhesive:	rubber, black	Elongation at break: <sup>1)</sup>	22 %
Adhesion on steel: <sup>1)</sup>	≥ 2,5 N/cm	Unwind strength:	9 mm: 2,0N/roll >9 mm: 6,0N/roll (v = 0,3m/min)
Total thickness: <sup>1)</sup>	0,3 mm	Temperature resistance: <sup>2) 3)</sup>	150° C/3.000h

<sup>1)</sup> Parameters of the specification 2) Application property 3) Depending on cable material

7200-05/06

tesa AG Quickbornstrasse 24 20253 Hamburg Germany Phone: +49-40 4909 3891 Fax: +49-40 4909 2265 tesa tape inc. 5825 Carniege Boulevard Charlotte, N.C. 28209, USA

tesa tape Asia Pacific Pte. Ltd. 164 Gul Circle Singapore 629621 Phone: +65-6861 2026 Phone: +1-704 554 07 07 Fax: +1-800 852 88 31 Fax: +65-6861 4790 www.tesatape.com www.tesa-asia.com

tesa products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best knowledge on the basis of our practical experience. Nevertheless tesa AG can make no warranties, express or implied, including, but not limited to, any implied warranty of merchantability of fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical staff will be glad to advise you.