

# tesa® 60954

## Anti-Slip Tape Heavy Duty



### Product Information

#### tesa® 60954 Anti-Slip Tape Heavy Duty

tesa® 60954 is an anti-slip tape with a highly-durable backing and designed for permanent heavy-duty applications, where good grip and safe footing is required, e.g. construction vehicles or platforms and ramps.

tesa® 60954 is a single-sided tape, with a paper liner, in form of a durable, hand-tearable anti-slip backing with an acrylic adhesive. The backing consists of a PVC film which is coated with large mineral particles and has been specifically developed for extreme conditions to provide extra slip resistance in heavy-duty applications. The acrylic adhesive provides an excellent bond to most surfaces.

The heavy duty anti-slip tape is certified according to DIN 51130 and available in the colors black, yellow, black-yellow and grey. The bright yellow and black-yellow colored tapes have a strong visibility for easy identification in areas of safety concerns and for warning purposes, a perfect solution for complementing 5S manufacturing initiatives.

#### Benefits:

- Highly-durable backing with extra slip resistance for extreme conditions
- Reduced clogging due to coarse particles
- Coefficient of friction: R13 according to DIN 51130 (R12 for black-yellow)
- Secure bonding to most surfaces
- Good chemical and weathering resistance
- Bright yellow and black-yellow colors ensure strong visibility for easy identification

#### Main Application

- Durable, slip resistant backing for heavy duty applications
- Construction vehicles, semi-trailers
- Platforms and ramps
- Forestry and agriculture equipment

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Technical Data

- |                    |  |                          |         |
|--------------------|--|--------------------------|---------|
| • Backing material | PVC film coated with large mineral particles | • Elongation at break    | 35 %    |
| • Total thickness  | 1185 µm                                      | • Tensile strength       | 40 N/cm |
| • Type of adhesive | acrylic                                      | • Temperature resistance | 80 °C   |

#### Adhesion to

- steel 7.0 N/cm

For latest information on this product please visit  
<http://l.tesa.com/?ip=60954>

# tesa® 60954



# Anti-Slip Tape Heavy Duty

## Product Information

### Properties

- Hand tearability ●●●
- Suitable for die cutting yes
- Resistance to chemicals ●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=60954>