

tesa® ACX^{plus} 7273 Multi Purpose (MP) 800 µm double-sided acrylic foam tape

tesa® ACX^{plus} 7273 MP is a gray double-sided acrylic foam tape.

The visco-elastic acrylic foam core of tesa® ACX^{plus} 7273 MP absorbs and dissipates dynamic and static loads. Due to this unique formulation, this double-sided acrylic foam tape is able to compensate for thermal elongations of bonded parts.

Main Application

The tesa® ACX^{plus} MP product family is suitable for a wide range of multi-purpose bonding applications.

To ensure the highest performance possible, our aim is to fully understand the application (including the substrates involved) in order to provide the right product recommendation.

tesa® ACX^{plus} 7273 MP series is especially suitable for bonding applications such as emblem, decorative part or signage mounting.

Technical Data

▪ Backing material	foamed acrylic	▪ Total thickness	800 µm
▪ Color	gray	▪ Type of adhesive	acrylic

Adhesion to

▪ Steel (after 3 days)	21.0 N/cm	▪ Aluminium (after 3 days)	35.0 N/cm
------------------------	-----------	----------------------------	-----------

Properties

▪ Temperature resistance short term	200 °C
-------------------------------------	--------

Additional Information

Please note that we recommend using tesa® Adhesion Promoter as a surface pre-treatment. It leads to a significant improvement in adhesion levels, avoids moisture infiltration, and promotes long-term resistance against harsh environmental factors. Which tesa® Adhesion Promoter should be used depends on the substrates and the application. We will be glad to advise you in order to find the right solution.

Liner versions:

- PV44: White filmic liner - branded

For latest information on this product please visit <http://l.tesa.com/?ip=07273>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.