

PRODUCT INFORMATION

Product: **PF565/80D Black/White**

Articlenumber: **3620904**

Description of the Product

Film backing:	Polyethylene
Colour:	black/white
Adhesive type:	Acrylic

Technical data

Thickness:	80µm	(QMP 21) *
Peel adhesion to stainless steel:	1.1+/-0.2 N/cm	(QMP 02) *
Breaking strength**		(QMP 03) *
Machine Direction (MD):	> 17 N/mm ²	
Transverse Direction (TD):	> 11 N/mm ²	
Elongation at break**		
Machine Direction (MD):	> 180 %	
Transverse Direction (TD):	> 380 %	

Application

The film **PF565/80D** is recommended for the protection of sensitive surfaces against dirt and damage during processing, storage and mounting e. g.

- rough painted metals
- rough plastic surfaces

Application conditions

- The surface must be free from oil, fat, dust and solvents
- Room temperature (> 10°C and < 40°C)

Resistance

- against moisture:	good
- against oil:	moderate
- against solvents:	moderate

Storage conditions of rolls

- Room temperature < 40°C
- Storage time max. 6 months after date of production

*QMP: internal method of measurement

** raw film data

Note: The data and recommendations are given in good faith, on the basis of practical experience, but without warranty. The customer should carry out own tests to confirm the use fullness of the product for the application under consideration. The technical data could have tolerances up to 15%.