



# Scapa 3305 Athletic Trainer Tape

## DESCRIPTION

Scapa 3305 is a high quality soft, conformable trainer tape consisting of a bleached cotton backing and a specifically formulated rubber adhesive containing zinc oxide for skin contact. It has been specifically designed for use by Athletics trainers/coaches when taping ankles, wrists, knees, etc Scapa 3305 is available in a bleached natural colour.

### **APPLICATIONS**

- Providing additional support for joints
- Helps prevent injuries
- Helps protect healing injuries

### **PRODUCT BENEFITS**

- Serrated edges on rolls allows easy tearing
- Soft, flexible and conformable
- Specially formulated skin friendly adhesive
- High tack and adhesion
- Easy to handle sized rolls

Issue: 1

Date: 02/07/02

Page 1 of 2

3305.doc

### www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer

## **TECHNICAL PROPERTIES**

	Unit	Nominal Value	Test Method
Nominal Thickness	mm	0.24	Internal*
Tensile Strength	N/cm	50	BS 3924
Adhesion to Steel	N/cm	5.0	BS 3924
Adhesion to Backing	N/cm	2.0	Internal*
Unwind force	N/cm	2.5	Internal*
Continuous Temperature	°C	60	Internal*

\*Scapa Internal Test Method

### STANDARD PRESENTATION

- Roll length: 10 m
- Roll width: 25, 38 and 50 mm
- Core: 25mm plastic core
- Packaging: Bulk packed in a reinforced carton for added protection

### RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°c and +25°c.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants Service life will vary with conditions of use and is affected by climatic environment, but it is recommended that the product should be used within 6 months of date of manufacture, if stored in a moderate climate and good

Issue: 1

conditions.

Date: 02/07/02

Page 2 of 2

3305.doc

### www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, it shall not, it shall not, its shall not extended application to respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer.