



## TECHNICAL DATA

# Scapa 9060S

## 60°C Paper Masking Adhesive Tape

### DESCRIPTION

**Scapa 9060S** is a 0.11 mm semi crepe paper tape coated with an aggressive rubber/resin solvent based adhesive system, recommended for all general purpose 60°C masking applications.

### APPLICATIONS

- Light weight bundling.
- Professional painters and plasters masking tape for indoor use.
- Suitable both for brush and spray air drying paints.
- Suitable for all general purpose 60°C indoor bonding, holding, sealing and masking applications.

### PRODUCT BENEFITS

- Clean removal at room temperature.
- Smooth and controlled unwind.
- Flexible and conformable.
- Good peel adhesion.
- Good shear and holding strength.
- Good paint flake resistance.
- Non staining.
- Resistant to mild chemicals, lacquers, solvents and water.
- Continuous temperature resistance: +60°C.

## TECHNICAL PROPERTIES

	Unit	Nominal value	Test Method
Total Thickness	mm	0.11	AFERA 4006
Tensile Strength	N/cm	30	AFERA 4004
Elongation at Break	%	10	AFERA 4005
Adhesion to Steel	N/cm	2.4	AFERA 4001

## STANDARD PRESENTATION

- Roll length: 50 metres
- Roll width: 12; 19; 25; 30; 38; 50; 75 and 100 mm
- Core: 76 mm Scapa branded cardboard core
- Packaging: Concertina
- Colour: Natural

## RECOMMENDATIONS

*The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.*

*Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.*

*Scapa masking tapes are not suitable for outdoor exposure and should not be submitted to prolonged periods of sunlight, as tapes may become difficult to remove. Clean removal may also vary with surface type, lacquers, primers and paints nature and the temperature of the surface at removal. For best results, remove the tape as soon as possible after applying the paints pulling it slowly at a 90° angle with constant speed.*