productinformation

tesa® 4651

Premium colored cloth tape

tesa® 4651 is a powerful high quality acrylic coated cloth tape. It is based on a 145 mesh woven rayon fabric backing and a natural rubber adhesive.

tesa® 4651 is a very strong cloth tape for almost every application.

Features:

- high adhesion even on rough surfaces
- excellent tensile strength
- straight tear edges longitudinal and horizontal
- easy to write on
- conformable
- available in 8 colors: black, white, grey, yellow, blue, red, green, brown

Main Application

- Indoor and outdoor applications
- High demanding applications
- Fixing, bundling, repairing, marking etc.
- Permanent sealing of pipes
- Securing of sharp edges
- Sandblasting

Technical Data

•	Backing material	acrylic-coated cloth	•	Elongation at break	13 %
•	Total thickness	310 μm		Tensile strength	100 N/cm
	Type of adhesive	natural rubber		Temperature resistance (30 min)	130 °C

Adhesian to steel 2.2 N/cm - Mach

Adhesion to steel 3.3 N/cm • Mesh 145 count per square inch

Properties

•	Hand tearability	••••		Suitable for die cutting	yes
	Straight tear edges	••••		Abrasion resistance	••••
•	Easy to write on	yes	•	Water resistance	•••

Evaluation across relevant tesa® assortment: ••• very good •• good • medium • low

Additional Information

Complies with LV 312-1 Dialectric strength.

For latest information on this product please visit http://l.tesa.com/?ip=04651

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 1 of 1 - As of 09/11/2018 - en