

tesa® 4939

tesa® 4939 is a double-sided floor laying tape. It consists of a strong PET-cloth backing in combination with a differential rubber adhesive system.

The special formulated adhesive on the open side combines a high initial bonding power with a residue free removability up to 14 days from the most common surfaces. (Needs to be tested individually before usage!)

Main Application

Temporary floor laying during fairs, exhibitions, conventions & renovations

Technical Data

▪ Backing material	cloth	▪ Elongation at break	40 %
▪ Color	white	▪ Tensile strength	50 N/cm
▪ Total thickness	250 µm	▪ Type of liner	glassine
▪ Type of adhesive	synthetic rubber	▪ Colour of liner	brown

Adhesion to

▪ Steel (initial)	5.0 N/cm	▪ Steel (after 14 days)	5.5 N/cm
▪ Steel (covered side, initial)	7.5 N/cm	▪ Steel (covered side, after 14 days)	8.0 N/cm
▪ PE (initial)	2.5 N/cm	▪ PE (after 14 days)	2.0 N/cm
▪ PE (covered side, initial)	4.5 N/cm	▪ PE (covered side, after 14 days)	5.0 N/cm
▪ PP (initial)	4.5 N/cm	▪ PP (after 14 days)	2.5 N/cm
▪ PP (covered side, initial)	6.5 N/cm	▪ PP (covered side, after 14 days)	5.0 N/cm

Properties

▪ Temperature resistance short term	80 °C	▪ Resistance to chemicals	● ● ● ●
▪ Temperature resistance long term	40 °C	▪ Static shear resistance at 23°C	● ● ● ●
▪ Tack	● ● ● ●	▪ Static shear resistance at 40°C	● ● ● ●
▪ Ageing resistance (UV)	● ●	▪ Static shear resistance at 70°C	● ●
▪ Humidity resistance	● ● ●	▪ Fogging	● ● ● ●

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04939>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.