productinformation

tesa® 4333 PV1 Precision Mask® Sensitive

High grade paper masking tape for precise and flat paint edges on sensitive surfaces

tesa® 4333 PV1 Precision Mask® Sensitive consists of an extra-thin and strong paper backing coated with a special acrylic adhesive.

The highly equipped and flat backing material makes the product highly conformable on various surfaces. Additionally the outstanding special adhesive formulation has got an application relevant adhesive power needed for masking applications on sensitive and critical surfaces. This allows an easy removability up to 1 week after application which enables multiple working processes in only one covering process.

Main Application

This tape is suited for almost all indoor paint works.
tesa® 4333 PV1 Precision Mask® Sensitive is applicable with water-based paints and lacquers and fits even for high-class spatula techniques.
It is especially designed for applications on sensitive and critical surfaces.
The flat backing material is highly conformable to the surface and leads to precise razor-sharp paint edges.

Technical Data

▪ Backing material	flat paper	▪ Adhesion to steel	0.5 N/cm
▪ Total thickness	80 µm	▪ Elongation at break	5 %
▪ Type of adhesive	acrylic	▪ Tensile strength	32 N/cm

Properties

▪ Suitable for sensitive surfaces	●●●●	▪ Paint anchorage	●●●●
▪ Suitable for rough surfaces	●●	▪ Sharp colour edge	●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit http://l.tesa.com/?ip=04333

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

tesa
great to work with