

tesa® 4441

Repulpable, Single-Sided Splicing Tape

tesa® 4441 is a single-sided repulpable splicing tape without liner consisting of an internally creped paper and a modified water soluble acrylic adhesive.

tesa® 4441 features especially

- Very high shear strength
- Very good stretching properties
- High tack properties
- Very good adhesion values on coated and uncoated paper
- Good repulpability over full pH-range (pH3 –pH9)

Colour: Light Blue, White

Main Application

tesa® 4441 is particularly suitable for:

- End tabbing applications
- General purpose applications

Technical Data

▪ Backing material	slightly-creped paper	▪ Tensile strength	75 N/cm
▪ Total thickness	140 µm	▪ Tensile strength (crosswise)	36 N/cm
▪ Type of adhesive	repulpable tackified acrylic	▪ Type of liner	none
▪ Elongation at break	11 %	▪ Shelf life time (packed) < 25°C	12 months

Properties

- | | | | |
|--------|-------|---------------------------|-------|
| ▪ Tack | ● ● ● | ▪ Static shear resistance | ● ● ● |
|--------|-------|---------------------------|-------|

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04441>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.