productinformation

tesa® Professional 50565 Professional

Strong 50µm aluminium duct tape with and without liner (PV1 and PV0)

tesa® 50565 is a robust aluminium duct tape comprising a substrate of aluminium foil and an acrylate adhesive mass. It has very good adhesive power and a high degree of heat conduction, making it very popular among craftsmen. Furthermore, the aluminium duct tape is resistant to moisture, is impermeable to water vapour and offers protection against oil and acids. The aluminium duct tape has low flammability, is easy to handle and is available with (PV1) and without release paper (PV0).

Main Application

- Indoor and outdoor applications
- Mounting of refrigeration coils
- Sealing of ducts
- General purpose temperature insulation
- Masking, protecting, repairing, closing

Technical Data

	Backing material	aluminium foil	Tensile strength	35 N/cm
•	Total thickness	90 μm	Temperature resistance min.	-40 °C
•	Type of adhesive	acrylic	Temperature resistance max.	160 °C
•	Adhesion to steel	6 N/cm	Surface finish	reflective
	Elongation at break	8 %		

Properties

Hand tearability Suitable for die cutting Certified according to	yes UL 510 Flame retardancy	:	Abrasion resistance Water resistance	•••

Evaluation across relevant tesa® assortment: •••• very good ••• good •• medium • low