

tesa® 4370

Cloth duct tape - 8 weeks UV resistant

tesa® 4370 is an 8 week UV-resistant cloth tape. It consists of a PE coated 70 mesh woven PET fabric backing and a black UV-blocker, coated with a pressure sensitive natural rubber adhesive. tesa® 4370 UV extra is suitable for long term protection of delicate areas like window frames, facades, and other surfaces during plastering and painting in construction sites. Features:

- 8 weeks UV resistance
- good adhesion, even on rough surfaces
- water repellent
- conformable
- easy to remove without residues
- easy to unwind
- available in white

Main Application

- Outdoor applications (up to 8 weeks)
- Protection of areas like window frames or facades during construction works
- Protection against dirt and damage through manufacturing tools and material
- Suitable for application on concrete/bricks, timber, glass

Technical Data

▪ Backing material	cloth	▪ Elongation at break	10 %
▪ Total thickness	310 µm	▪ Tensile strength	60 N/cm
▪ Type of adhesive	natural rubber	▪ UV-resistance	8 weeks
▪ Adhesion to steel	3.8 N/cm	▪ Mesh	70 count per square inch

Properties

▪ Hand tearability	● ● ●	▪ Paint anchorage	● ● ●
▪ Suitable for sensitive surfaces	● ● ●	▪ Conformability	● ● ●
▪ Suitable for rough surfaces	● ● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

Additional Information

Recommendation: please conduct a test on the application surface before using the product.

For latest information on this product please visit <http://l.tesa.com/?ip=04370>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.