

tesa® 4308

Masking tape for high demanding applications

tesa® 4308 is a slightly crêped paper masking tape which has been developed especially for high demanding masking applications in the automotive refinish and transportation industry.

tesa® 4308 withstands temperatures up to 100°C. It can be used either with 2 component or water based paints. The backing avoids penetration of lacquer or paint.

tesa® 4308 can be removed easily without any residues and leaving sharp paint edges.

Main Application

- Ambitious lacquering work
- Clean paint edges
- Protection of delicate surfaces

Technical Data

▪ Backing material	slightly-creped paper	▪ Elongation at break	13 %
▪ Total thickness	170 µm	▪ Tensile strength	53 N/cm
▪ Type of adhesive	natural rubber	▪ Temperature resistance	100 °C
▪ Adhesion to steel	4 N/cm		

Properties

▪ Hand tearability	● ● ● ●	▪ Sharp colour edge	● ● ● ●
▪ Easy to remove	yes	▪ Conformability	● ● ●
▪ Paint anchorage	● ● ● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04308>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.