

tesa® 7006

Low tack masking tape

tesa® Mask, „Sensitive“ is a low tack and flexible paper masking tape for delicate surfaces.

The tape is available with one or two adhesive-coated edges and fully coated and is available in different widths.

Removal of the tape is easy and residue free.

Main Application

Due to the low adhesion power the tape is especially suitable for sensitive applications like e.g. masking of wallpapers or freshly painted surfaces. The tape will be removed easily and residue-free.

Technical Data

▪ Backing material	slightly-creped paper	▪ Elongation at break	10 %
▪ Total thickness	120 µm	▪ Tensile strength	37 N/cm
▪ Type of adhesive	acrylic	▪ UV-resistance	1 weeks
▪ Adhesion to steel	0.3 N/cm		

Properties

▪ Hand tearability	● ● ● ●	▪ Smooth colour edge	● ● ●
▪ Suitable for sensitive surfaces	● ● ● ●	▪ Conformability	● ● ● ●
▪ Paint anchorage	● ● ● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

Additional Information

Please note that adhesive tapes should not be left on sensitive surfaces for longer than one week as residues during the de-masking might occur after that. Before using an adhesive tape on a delicate surface, please make a trial application for up to 24 hours.

For latest information on this product please visit <http://l.tesa.com/?ip=07006>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.