

tesa® 4348

Flexible masking tape for indoor painting applications

tesa® 4348 is a finely creped paper masking tape with a natural rubber adhesive.

Main Application

- Indoor applications
- Clean edges to paint and lacquer
- For smooth surfaces
- For simple painting tasks

Technical Data

▪ Backing material	slightly-creped paper	▪ Adhesion to steel	3.3 N/cm
▪ Total thickness	140 µm	▪ Elongation at break	10 %
▪ Type of adhesive	natural rubber	▪ Tensile strength	36 N/cm

Properties

▪ Hand tearability	● ● ● ●	▪ Sharp colour edge	● ● ●
▪ Suitable for rough surfaces	● ●	▪ Conformability	● ● ●
▪ Paint anchorage	● ● ● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

Additional Information

tesa® 4348 features a high immediate bond and can be removed without leaving any adhesive residue.

For latest information on this product please visit <http://l.tesa.com/?ip=04348>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.