



TECHNICAL DATA

Scapa 1129

Cellulose Lithographic Adhesive Tape

DESCRIPTION

Scapa 1129 is a dark red dyed release coated cellulose film single coated with a solvent based rubber/resin adhesive with 45µm total thickness. Recommended for edging, masking, stripping and splicing applications.

APPLICATIONS

- Suitable for the printing and graphic industry, for photographic films.
- Protects orthochromatic films, contact and enlarging papers, printing plates during light exposure.
- Ruby red colour allows an accurate positioning of the tape on stored films.
- Not suitable for use in conditions of high humidity.

PRODUCT BENEFITS

- Anti-static
- Biodegradable
- Clean removal from photographic films
- Easy unwind
- Hand tearable
- Optically transparent and photographically opaque
- Red colour enables easy identification
- Service temperature: -10°C to +100°C (up to 130°C for short period)

TECHNICAL PROPERTIES

	Unit	Nominal value	Test Method
Total Thickness	mm	0.045	AFERA 4006
Tensile Strength	N/cm	40	AFERA 4004
Elongation at Break	%	23	AFERA 4005
Adhesion to Steel	N/25mm	6	AFERA 4001

STANDARD PRESENTATION

- Roll length : 66 metres
- Roll width : 12, 15, 19, 25, 38 and 50 mm
- Core : 76 mm Scapa branded cardboard core
- Packaging : Sleeve pack (for 12 to 25mm) – Bags (38 and 50mm)
- Colour : Dark Red

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes.

Cellulose based products are sensitive to heat, moisture and storage conditions. When stored in their original carton at recommended conditions of +23°C and 50% humidity, the best usage date will be within 6 months from the date of shipment.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.