

Economy Grade Duct Tape

Product Description

Economy grade, PE laminated synthetic cloth duct tape, coated with synthetic rubber – resin solvent free adhesive. Characterized by excellent conformability, adhesion to multiple surfaces, semi-permanent bond and good tensile strength, it is suitable for bundling, sealing, repairing operations in many DIY Projects. UV exposure not recommended.

Features

- Easy tear
- Good holding power
- Good tensile strength
- Excellent conformability
- Suitable for multiple surfaces
- Perfectly waterproof

Main Applications

- Bundling, sealing, temporary repairing operations
- Non - critical pipe wrapping and duct seaming
- Double glazing unit sealing
- General maintenance and protection
- Color coding and marking

Technical Data

	Metric	Imperial Units	Test Method
Total weight*	110 g/m2	110 g/m2	ISO 536
Total thickness*	145 µm	5.7 mils	Internal
MD tensile strength*	35 N/cm	20 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	20 %	20 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	7 N/cm	64 oz/in	AFERA 5001/PSTC 101

Backing material

PE laminated synthetic cloth

Type of adhesive

Synthetic rubber resin - solvent free

*Typical value

Available colour



Silver



Black



White

Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. The company reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of manufacture. The company does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.