

TECHNICAL DATA SHEET

N.E.C. APPROVED EXHIBITION CARPET TAPE

Double-sided Peel-Perm LDPE Tape

DESCRIPTION

The tape is a Printed 60 micron Low Density Polyethylene Film carrier. It is coated on the Open Side with a Low-Tack Peelable adhesive and on the closed side with a High-Tack Permanent adhesive, with an 80gsm White Glassine Release Liner, which is sideways-tearable.

TYPICAL APPLICATION

The tape is ideally suited for temporary carpet-laying, as at exhibitions.

APPLICATION

The Open Side (i.e. That which is exposed as the tape is wound off the roll) is applied to the Exhibition Floor, which must be clean, and the Release Liner removed to expose the Permanent adhesive on to which the underside of the Exhibition Carpet is firmly placed. The peelable side to the floor can therefore be removed without leaving residue.

TECHNICAL DETAILS

TYPICAL VALUES

Adhesive Colour	Clear
Adhesive Type	Pure Acrylic
Tape Thickness (Carrier & Adh)	0.108mm
Carrier Thickness	0.060
Peel Adhesive (steel) 24hrs	120/920N/M
Loop Tack	140/640N/M
Shear Static (Hrs @ 1KG)	1/120
Temp °C Min Application	+5°C /-5°C
Service Range	-20 to +120°C
Shelf Life	12mths PSTMA Conditions

Warranties

These figures are average values and should not be regarded as maximum or minimum values for specification purposes.

All statements, technical information and recommendations about **Shand Higson & Co Ltd** products are based on tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold on the basis that the purchaser shall make their own tests to determine the suitability of such products for their particular applications and uses, and that the purchaser assumes all risks and liabilities for the results of the use of the products, including use in accordance with the seller's recommendations.

No salesman, representative or agent of **Shand Higson & Co Ltd** is authorised to give any guarantee, warranty or make any representation contrary to the above.