Date of Issue 06/06/2016

Rev. 00 06/06/2016

# **PVC** Floor Marking Tape

### **Product Description**

274 is a PVC floor-marking tape for indoor use, coated with a natural rubber adhesive used for factory demarcation areas and sports court marking.

#### **Features Main Applications**

- High Adhesion
- Abrasion Resistant

- Identifying factory demarcation areas
- · Sports court marking

Technical Data			
	Units	Std. Values	
Total Thickness	μm	150	
MD tensile strength	N/cm	27	
MD elongation at break	%	160	
Peel Adhesion	N/cm	1.2	
Service Temperature (up to)	°C	80	

#### **Backing material**

Type of adhesive

Natural Rubber (Solvent Borne)

## Available colour













#### Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. The company reminds the user of the products to make sure that the product is used as per the instructions and suggestions provied. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Studges that a share a line in the sun direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of manufacture. The company does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.