

# Technical Data Sheet

## Deemark Builders Tape

### Product Description

- Soft PVC tape suitably plasticised and stabilised
- Coated with rubber-based pressure sensitive adhesive on one side
- Easy-unwind protective tape
- Specially formulated FR self-extinguishing tape

### Applications

- Surface protection for general materials
- Ideal for masking aluminum, UPVC and painted wooden window and door frames

### Features/Benefits

- Weather resistant
- Limited UV-resistance
- No known hazards
- RoHS 2011/65/EU( 2015/863/EU); REACH SVHC

### Technical Performance

Description	Units	Value	Test method
Tape thickness	mm/mils	0.110 / 4.3	ASTM D-1000
Adhesion to steel	kg/cm, oz/in	0.14 / 12.5	ASTM D-1000
Elongation at break	%	180	ASTM D-1000
Tensile Strength	kg/cm, lbs/in	1.8 / 10.05	ASTM D-1000


### Storage Details

- Recommended one-year shelf life from date of dispatch if kept at moderate temperatures and humidity levels

### Important Notice

Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use.

Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture as of the date of purchase. **WE MAKE NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at our option, to replace or repair the product or refund the purchase price of the product. Except where prohibited by law, we will not be liable for any loss or damage arising from this product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.



# Test Report

	Measurement
1. Visual	OK
2. Thickness (mm)	0.1
3. Adhesion (kg/25mm)	0.52
4. Unwinding Force (kg/25mm)	0.15
5. Tensile Strength (kg/25mm)	4.5↑
6. Elongation (%)	180↑
7. REACH SVHC	OK
Test Date : APR. 07. 2022Temp. : 23°C R.H. : 50%	