

TECHNICAL DATA

Product datasheet Issue No 7

Issued Jan 2020

R032012 DOUBLE-SIDED TISSUE TAPE ECONOMY GRADE

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Adhesive type: Pressure-sensitive hotmelt rubber/resin		
Thickness, adhesive + carrier	0.080	mm
Release liner thickness	0.055	mm
180 degree peel adhesion:		
Open side	N/A	N/m
Closed side	N/A	N/m
Polyester loop tack:		
Open side	1200	N/m
Closed side	1200	N/m
Liner release	65	gsm
Tensile strength	1200	N/m
Elongation at break	10	%
Service temperature	-10 to +60	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	50	Hours
Shelf life	12	Months

Test Methods: BS 7116

This product is also available in fingerlift form.

Standard formats 6/12, 9/15, 12/18, 18/24, 24/30. Other formats, including offset fingerlift available subject to minimum order quantities.

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.