

TECHNICAL DATA

Issue No 3 Issued June 2015

C10TRIM DOUBLE-SIDED POLYETHYLENE FOAM TAPE MODIFIED ACRYLIC ADHESIVE

<u>TECHNICAL DETAILS</u>		<u>TYPICAL VALUE</u>	<u>UNITS</u>
Adhesive type		Emulsion Modified Acrylic	
180 degree peel adhesion:		> Internal strength of foam	N/m
Foam Density - Black foam		67	Kg per cu. Metre
Foam Density - White foam		50	Kg per cu. Metre
Shore hardness		53	00 scale
Force to compress by 25%		40	kPa
Liner type		Amber	
Liner release		10	N/m
Tensile strength	MD	650	kPa
	CD	430	kPa
Elongation at break	MD	310	%
	CD	430	%
Service temperature		-20 to +120	Deg. C.
Recommended application temperature		+5 to +25	Deg. C.
UV resistance		Excellent	
Fungi resistance		Excellent	
Weather resistance		Excellent	
Shelf life		12	Months
THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY. ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.			