

R031010SIL — Aluminium Foil Tape

Technical Data

Description	A 30 micron soft tempered bright aluminium foil coated with a pure acrylic adhesive, particularly suited to very low temperatures, on a 60gsm honey glassine liner. Building Regulations Class 0 approved which correlates to EN13501- 1 Class B	
Construction	Carrier:	30µ soft tempered bright aluminium foil
	Adhesive:	WM1070 pure acrylic permanent
	Release liner:	60gsm siliconised honey glassine
	Tape Thickness:	0.060 mm (without liner)
	Carrier Thickness:	0.030 mm
	Adhesive colour:	clear

Typical Application This product is recommended where a moisture barrier is required.

Typical Physical Properties	These figures are average values and should not be regarded as maximum or minimum values for specification purposes.	
	Peel Adhesion Steel (24 hours) FINAT FTM1	- 20 N/25mm
	Initial Tack Steel FINAT FTM9	- 10 N/25mm
	Static Shear (hrs @ 1kg) FINAT FTM8	- 30 hours
	Recommended temp. application range	- 5 to 38°C
	Shelf Life	- 12 months PSMA conditions

Warranties

All statements, technical information and recommendations about this product are based on tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold on the basis that the purchaser shall make their own tests to determine the suitability of such products for their particular applications and uses, and that the purchaser assumes all risks and liabilities for the results of the use of the products, including use in accordance with the seller's recommendations. No salesman, representative or agent is authorised to give any guarantee, warranty or make any representation contrary to the above.