

2000 SERIES

TECHNICAL DATA

Product datasheet Issue No 5 Issued Sept 2015

RA 2300/2305 EURATRANS PERMANENT REINFORCED TRANSFER TAPE

2300 on std. 76mm cores 2305 on 25mm dispenser cores

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin		
Thickness, adhesive + carrier	0.070	mm
Release liner type	White glassine printed 'EuRatrans'	
Release liner thickness	0.055	mm
180 degree peel adhesion:		
Open side	1200	N/m
Closed side	1400	N/m
Polyester loop tack:		
Open side	1400	N/m
Closed side	1100	N/m
Liner release	10	N/m
Service temperature	-40 to +60	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shelf life	12	Months
Test Methods: BS 7116		

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.