

Product datasheet Issue No 9

Issued Feb 2014

2735 DOUBLE-SIDED ECONOMY FINGERLIFT TISSUE TAPE, WHITE LINER

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin		
Thickness, adhesive + carrier	0.080	mm
Release liner thickness	0.055	
180 degree peel adhesion: Open side	900	N/m
Closed side	900	N/m
Polyester loop tack: Open side	1000	N/m
Closed side	1000	N/m
Liner release	10	N/m
Tensile strength	1200	N/m
Elongation at break	10	%
Service temperature	-10 to +60	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	Greater than 100	Hours
Shelf life	12	Months
Standard product formats	6/12, 9/15, 12/18, 18/24, 24/30 Other formats, inc. offset fingerlift available subject to min. quantities	
Test Methods		BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.