



EUROCEL PP 5231

Short description:

Single sided packaging tape

Product Data

Backing:	0.025 mm BOPP film
Adhesive:	synthetic rubber, transparent-brown
Total thickness	0.041 mm
Adhesion to steel	9 N/25mm
Tensile strength MD	100 N/25mm
Elongation at break	140 %
Temp. Resistance	60 °C

Application

Standard carton sealing tape, suitable for most common use.
Low backing thickness version of EURO PP 31.

Features	Benefits
Synthetic rubber adhesive	<ul style="list-style-type: none"> ➤ High tack ➤ Performing well in most common use
Bopp backing	<ul style="list-style-type: none"> ➤ Well adaptable to different shapes ➤ Good elongation

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use.

SICAD S.p.A., Via Caduti della Liberazione, 57 21040 Uboldo (VA) - ITALY
Tel.+39 02 96412.1; Fax +39 02 96412322 export market;
Fax +39 02 96780832 domestic market; www.eurocel.it

This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss