

tesa® 4100

General purpose carton sealing tape

tesa® 4100 is based on a PVC backing coated with a natural rubber adhesive.

Due to its embossed film texture an even and smooth unwind is guaranteed. Additionally the embossed surface prevents reflection during e.g. barcode reading; therefore the product is perfectly suited to label protection.

The easy unwinding feature encourages the usage of tesa® 4100 in automatic sealing equipment.

The process of cardboard waste recycling is not affected as confirmed by leading recycling companies and paper mills.

Main Application

tesa® 4100 is used for manual and automatic sealing of cartons of medium weight.

Technical Data

▪ Backing material	PVC film	▪ Adhesion to steel	2.2 N/cm
▪ Total thickness	65 µm	▪ Elongation at break	75 %
▪ Type of adhesive	natural rubber	▪ Tensile strength	47 N/cm

Properties

▪ Automatic application	yes	▪ Printability	● ● ● ●
▪ Manual application	yes	▪ Low noise unwinding	yes

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

Additional Information

tesa® 4100 is easily printable. Available colours: white, havana and transparent

For latest information on this product please visit <http://l.tesa.com/?ip=04100>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.