

tesa® 51300

Heat-resistant universal bandoliering tape

This tape consists of a crêped paper with a heat-resistant thermosetting adhesive.

For short term exposure, the maximum applicable temperature is 180 °C.

Main Application

The product is therefore particularly suitable for bandoliering of components which, as part of the production process, have to pass through a drying zone after lacquering, or are exposed to artificial ageing by heat.

Due to the age-resistant adhesive, tesa® 51300 is especially suitable for stock-belting.

Technical Data

▪ Backing material	slightly-creped paper	▪ Elongation at break	12 %
▪ Total thickness	165 µm	▪ Tensile strength	42 N/cm
▪ Type of adhesive	natural rubber	▪ Temperature resistance	140 °C
▪ Adhesion to steel	4.1 N/cm		

Additional Information

Colours: chamois, blue

For latest information on this product please visit <http://l.tesa.com/?ip=51300>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.