

Scapa 4405

General Purpose u-PVC Double Sided Tape - cross linked rubber adhesive, white liner,
0.1mm

DESCRIPTION

Scapa 4405 is a general purpose double sided tape based on a UPVC film. The tape is coated on both sides with a solvent rubber based adhesive system with an 82gr. white siliconised paper release liner, resulting in a total thickness of 0.10 mm. Recommended for general purpose bonding, mounting and splicing applications.

APPLICATIONS

- Show card assembly.
- Mounting sample cards.
- For self-locating creasing matrix systems for the packaging industry.
- Mounting display items.
- General purpose splicing tape except for siliconised films and papers.

PRODUCT BENEFITS

- Service temperature: -10°C to +70°C.
- Not recommended for direct exposure to sunlight or UV.
- High tack.
- Clean removal after use.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	12	N/25mm	AFERA 5001
Elongation at Break	75	%	AFERA 5004
Liner Thickness	69	µm	AFERA 5006
Tensile Strength	60	N/cm	AFERA 5004
Total Thickness (Without Liner)	100	µm	AFERA 5006

STANDARD PRESENTATIONS

- Colours: Translucent
- Core: 76mm Scapa branded cardboard
- Roll Width: 12, 19, 25, 38, 50, 75 and 1,355 mm
- Roll Length: 33 metres

Note:

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the shelf life of the tape is 12 months from the date of dispatch. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants