



TECHNICAL DATA

Scapa A1179

Acrylic Foam Tape

DESCRIPTION

Scapa A1179 is a 1.1mm thick standard performance acrylic foam bonding tape. The product is available in white. Scapa A1179 consists of an acrylic foam adhesive with a solid acrylic core and a Scapa branded paper release liner.

APPLICATIONS

- Signage manufacturing.
- Trim attachment.
- Metal stiffener bonding.
- Georgian bars.

PRODUCT BENEFITS

- Service Temperature -30°C to $+80^{\circ}\text{C}$ {continuous}
- Temperature Short Term Performance Range -30°C to $+130^{\circ}\text{C}$ {maximum duration of 1 hour}
- Consisting of a high quality pressure sensitive acrylic adhesive
- Good resistance to moisture and plasticiser
- Very good Ultra violet {UV} light resistant
- Resistance to abrasion, corrosion and moisture
- Suitable for indoor and outdoor environments
- No known hazards associated with this product
- Pre-determined dimensional bonding tape reduces waste
- Clean to use

TECHNICAL PROPERTIES

	Unit	Nominal Value	Test Method
180° Peel Adhesion	N/25mm	40	Scapa F9
Dynamic Shear	Ncm ⁻²	53	Scapa F11
Static Shear {1Kg/6.25cm ² }	Hours	500+	Scapa F7
Rolling Ball Tack Test	mm	310	Scapa F 23

STANDARD PRESENTATION

- Formats: Logs, Rolls
- Thickness: 1.1 mm (± 0.1)
- Core: 76mm

RECOMMENDATIONS

Surfaces must be clean, dry, free from grease and dirt.

Recommended cleaning agent is Propan-2-ol, {IPA}. Please note manufacturer's safety instructions should be followed and customers are recommended to ensure compatibility of the solvent with their substrate.

Ideal bonding substrates are those which are: clean, dry, flat, smooth, dust free & non-porous

Application temperature: +10 °C to + 40 °C. Shelf life of 1 year

Low temperatures may increase the risk of condensation, reducing the tack of the product.

Life expectancy will vary with temperature and humidity.

Product may be applied by hand direct from a roll applying even pressure.

Customers are recommended to make their own assessment of our products under their own conditions, for their own requirements.

www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer.