



TECHNICAL DATA

Scapa 1112

Red Cellulose Adhesive Tape

DESCRIPTION

Scapa 1112 is a clear release coated cellulose film coated with a red pigmented solvent based rubber/resin adhesive, with 57 μ total thickness and recommended for splicing applications.

APPLICATIONS

- Suitable for general splicing applications with exception of siliconised substrates.

PRODUCT BENEFITS

- Anti-static.
- Biodegradable.
- Easy unwind.
- Easy splice identification thanks to the red coloured adhesive.
- Hand tearable.
- High tack.
- Service temperature: -15°C to +100°C.

TECHNICAL PROPERTIES

	Unit	Nominal value	Test Method
Total Thickness	mm	0.057	AFERA 4006
Tensile Strength	N/cm	36	AFERA 4004
Elongation at Break	%	20	AFERA 4005
Adhesion to Steel	N/cm	3	AFERA 4001

STANDARD PRESENTATION

- Roll length : 66 metres
- Roll width : 19, 25, 30, 38 and 50 mm
- Core : 76 mm Scapa branded cardboard core
- Packaging : Concertina
- Colour : Red

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes.

Cellulose based products are sensitive to heat and moisture and life expectancy can vary with the storage conditions. When stored in their original carton at recommended conditions of +23°C and 50% relative humidity, shelf life will be of 6 months from the date of shipment.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.