

TECHNICAL DATA

Scapa 3302

Uncoated Cotton Cloth Tape

DESCRIPTION

Scapa 3302 is a general purpose, coloured, uncoated cotton cloth tape with a pressure sensitive adhesive Scapa 3302 is available in a wide variety of colours

APPLICATIONS

- Sealing and identification for example flight cases, film canisters or magazines
- Floor marking on stages, film sets etc
- General purpose applications such as colour coding, packaging, masking and protection and identification

PRODUCT BENEFITS

- Corrosion resistant
- Abrasion resistant
- Available in a wide range of colours for identification and colour coding applications
- Highly conformable and flexible
- Good unwind properties
- Good initial tack and ultimate adhesion
- Easy tear by hand
- Strong and durable
- Can be written on
- Certain colours can be supplied to DEF STAN 75-2 specification (olive green, buff/ tan, white)
- Service Temperature of 0 to +60 °C

| Issue : 3 |
|-----------|
|-----------|

Date : 01/12/02

Page 1 of 2

3302.doc

www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer.

TECHNICAL PROPERTIES

| Description | Units | Nominal Value | Test Method |
|-------------------|-------|---------------|-------------|
| Thickness | mm | 0.25 | Internal* |
| Adhesion to Steel | N/cm | 2.8 | IEC 454-2 |
| Tensile Strength | N/cm | 70 | IEC 454-2 |

STANDARD PRESENTATION

- Roll Length: 25m, 50m
- Roll Width: 19mm, 25mm, 38mm, 50mm, 75mm, 100mm
- Core: Cardboard
- Packaging: Scapa branded, bulk packed using interleaved sheets between layers

Note: Information on non-standard sizes and lead times are available on request.

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants Service life will vary with conditions of use and is affected by climatic environment, but it is recommended that the product should be used within 6 months of date of manufacture, if stored in a moderate climate and good conditions.

Issue : 3

Page 2 of 2

3302.doc

www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, it shall not, it shall not, its shall not extended application to respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer.